



SOLIDEAL L2/G2/E2 • L3/G3/E3 • RM L3/E3 • SKZ • RM L4/E4

## Bias tires

TIRE SIZE	PR	TREAD PATTERN	TT / TBLS	RIM SIZE RECOMMENDED <sup>(1)</sup>	ACTUAL TIRE DIMENSIONS						INFLATION PRESSURE		LOAD CAPACITY <sup>(2)</sup>	
					Overall diameter		Overall width		Original tread depth		bar	PSI	10 km/h • 6 mph	
					mm	inch	mm	inch	mm	32nd			kg	lbs
15.5 - 25	12	L2/G2/E2	TBLS	12.00 / 1.3	1272	50.1	408	16.1	26	33	4.00	57	5600	12350
15.5 - 25	12	L3/G3/E3	TBLS	12.00 / 1.3	1283	50.5	417	16.4	26	33	4.00	57	5600	12350
15.5 - 25	16	L2/G2/E2	TBLS	12.00 / 1.3	1274	50.2	414	16.3	26	33	5.50	79	6900	15250
15.5 - 25	16	L3/G3/E3	TBLS	12.00 / 1.3	1285	50.6	407	16.0	26	33	5.50	79	6900	15250
17.5 - 25	12	L2/G2/E2	TBLS	14.00 / 1.5	1350	53.1	385	15.2	26	33	3.50	50	6150	13600
17.5 - 25	12	L3/G3/E3	TBLS	14.00 / 1.5	1380	54.3	467	18.4	26	33	3.50	50	6150	13600
17.5 - 25	16	L2/G2/E2	TBLS	14.00 / 1.5	1337	52.6	460	18.1	26	33	4.75	68	7300	16100
17.5 - 25	16	L3/G3/E3	TBLS	14.00 / 1.5	1391	54.8	460	18.1	26	33	4.75	68	7300	16100
17.5 - 25	16	RM L3/E3	TBLS	14.00 / 1.5	1350	53.1	445	17.5	30	38	4.75	68	7300	16100
17.5 - 25	20	L3/G3/E3	TBLS	14.00 / 1.5	1363	53.7	477	18.8	26	33	5.75	82	8250	18200
20.5 - 25	16	L2/G2/E2	TBLS	17.00 / 2.0	1506	59.3	535	21.1	30	38	3.50	50	8250	18200
20.5 - 25	16	L3/G3/E3	TBLS	17.00 / 2.0	1503	59.2	545	21.5	32	40	3.50	50	8250	18200
20.5 - 25	16	SKZ	TBLS	17.00 / 2.0	1505	59.3	561	22.1	33	42	3.50	50	8250	18200
20.5 - 25	20	L2/G2/E2	TBLS	17.00 / 2.0	1487	58.5	550	21.7	30	38	4.50	64	9500	20950
20.5 - 25	20	L3/G3/E3	TBLS	17.00 / 2.0	1512	59.5	552	21.7	32	40	4.50	64	9500	20950
20.5 - 25	20	RM L3/E3	TBLS	17.00 / 2.0	1490	58.7	520	20.5	32	40	4.50	64	9500	20950
23.5 - 25	20	L3/G3/E3	TBLS	19.50 / 2.5	1620	63.8	635	25.0	37	47	3.75	54	10900	24050
23.5 - 25	20	RM L3/E3	TBLS	19.50 / 2.5	1615	63.6	595	23.4	36	45	3.75	54	10900	24050
23.5 - 25	24	L3/G3/E3	TBLS	19.50 / 2.5	1630	64.2	630	24.8	37	47	4.75	68	12500	27600
26.5 - 25	20	L3/G3/E3	TBLS	22.00 / 3.0	1752	69.0	691	27.2	40	50	3.50	50	13200	29150
26.5 - 25	28	L3/G3/E3	TBLS	22.00 / 3.0	1767	69.6	690	27.2	40	50	4.75	68	15500	34200
26.5 - 25	28	RM L3/E3	TBLS	22.00 / 3.0	1750	68.9	675	26.6	37	47	4.75	68	15500	34200
29.5 - 25	28	L3/G3/E3	TBLS	25.00 / 3.5	1873	73.7	770	30.3	36	45	4.25	61	17500	38650
29.5 - 25	28	RM L3/E3	TBLS	25.00 / 3.5	1875	73.8	750	29.5	42	53	4.25	61	17500	38650
29.5 - 29	40	RM L4/E4	TBLS	25.00 / 3.5	1975	77.8	750	29.5	61	77	6.25	89	23600	52100



## Radial tires

TIRE SIZE	STAR RATING	TREAD PATTERN	TT / TBLS	RIM SIZE RECOMMENDED <sup>(1)</sup>	ACTUAL TIRE DIMENSIONS						INFLATION PRESSURE		LOAD CAPACITY <sup>(2)</sup>	
					Overall diameter		Overall width		Original tread depth		bar	PSI	10 km/h • 6 mph	
					mm	inch	mm	inch	mm	32nd			kg	lbs
17.5 R 25	Dual Star ® **	SRGP	TBLS	14.00 / 1.5	1348	53	469	18	28	35	6.50	93	8500	18750
17.5 R 25	Dual Star ® **	SRLS L5S	TBLS	14.00 / 1.5	1399	55	445	18	77	96	6.50	93	8500	18750
20.5 R 25	Dual Star ® **	SRGP	TBLS	17.00 / 2.0	1492	59	548	22	33	42	6.50	93	11500	25400
20.5 R 25	Dual Star ® **	SRAT	TBLS	17.00 / 2.0	1493	59	521	21	32	40	6.50	93	11500	25400
20.5 R 25	Dual Star ® **	SRLD L5	TBLS	17.00 / 2.0	1548	61	520	20	77	96	6.50	93	11500	25400
23.5 R 25	Dual Star ® **	SRGP	TBLS	19.50 / 2.5	1615	64	624	25	35	44	6.50	93	14500	32000
23.5 R 25	Dual Star ® **	SRAT	TBLS	19.50 / 2.5	1617	64	597	24	35	44	6.50	93	14500	32000
23.5 R 25	Dual Star ® **	SRLD L5	TBLS	19.50 / 2.5	1673	66	597	24	83	105	6.50	93	14500	32000
23.5 R 25	Dual Star ® **	SRLS L5S	TBLS	19.50 / 2.5	1673	66	597	24	83	105	6.50	93	14500	32000
26.5 R 25	Dual Star ® **	SRGP	TBLS	22.00 / 3.0	1746	69	704	28	40	50	6.50	93	18500	40850
26.5 R 25	Dual Star ® **	SRAT	TBLS	22.00 / 3.0	1750	69	673	26	40	50	6.50	93	18500	40850
26.5 R 25	Dual Star ® **	SRLD L5	TBLS	22.00 / 3.0	1798	71	673	26	90	113	6.50	93	18500	40850
26.5 R 25	Dual Star ® **	SRLS L5S	TBLS	22.00 / 3.0	1798	71	673	26	95	120	6.50	93	18500	40850
29.5 R 25	Dual Star ® **	SRGP	TBLS	25.00 / 3.5	1870	74	782	31	40	50	6.50	93	22400	49450
29.5 R 25	Dual Star ® **	SRAT	TBLS	25.00 / 3.5	1874	74	749	29	40	50	6.50	93	22400	49450
29.5 R 25	Dual Star ® **	SRLD L5	TBLS	25.00 / 3.5	1921	76	750	30	95	120	6.50	93	22400	49450
29.5 R 29	Dual Star ® **	SRLS L5S	TBLS	25.00 / 3.5	2023	80	750	30	105	132	5.75	82	23600	52100

### Remarks

(1) Check rim for size, especially on width, as this should correspond to tire base marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. For details please contact the technical department. Loads are valid for intermittent service only, they do not include the additional weight of the tires.